FASTENING PLYWOOD TO

	FASTENER	PULL-OUT-FORCE	SIZE	FASTENER	
SINGLE POUR (YELLOW)	E-BEAM Nail (Yellow) (#4 Box, 1,000/box) EFCO ITEM #10890	160 lb (73 kg)	.100" x 1 1/2" (2.5 mm x 38 mm)		
MULTIPLE POURS (GREEN)	E-BEAM Nail (Green) (#4 Box, 1,000/box) EFCO ITEM #12890	410 lb (186 kg)	.100" x 1 1/2" (2.5 mm x 38 mm)		FCO
	E-BEAM Nail (Green Collated) (250/coil 4,000/box) EFCO ITEM #09890	410 lb (186 kg)	.100" x 1 1/2" (2.5 mm x 38 mm)		AVAILABLE THROUGH EFCO
FASTENERS PULLS THROUGH PLYWOOD (RED)	Self-Drilling Screw 1 5/8" (41 mm) (100/bag) SDS PH FL Reamer #3PT Zinc Plated EFCO ITEM #11890	500 lb (228 kg)	#10-16 x 1 5/8" (M5 x .08 mm x 41 mm)		AVAII
	Self-Drilling Screw 2 1/4" (57 mm) (100/bag) SDS PH FL Reamer #3PT Life Coat EFCO ITEM #13890	500 lb (228 kg)	#8-18 x 2 1/4" (M4 x .07 mm x 57 mm)		
	Screw 1 5/8" (41 mm) Automatic Feed for 3/4" (19 mm) Material. SouthernCarlson 1-515-986-5287. 1 5/8" (41 mm) Wood to Steel Wing tipped Self-Drilling Screw SENCO ITEM #08G162CTWFWS	500 lb (228 kg)	1 5/8" (41 mm)		CUSTOMER TO SOURCE LOCALLY
PLYWOOD TO INSERT ANGLE	Elevator Bolt 1/4" (6 mm) x 1 1/2" (38 mm) for plywood to insert angle	NOT TESTED	1/4" x 1 1/2" (6 mm x 38 mm)		CUSTOMER
AUTO	I-FEED CORDED SCREWDRIVER D MODEL DS235-AC-5,000 RPM	FASCO NAIL GUN MODEL F44AC CN15W-PS65 CONTACT: 1-800-239-8665	MULTIPLE-POUR NAILING PATTERN	RECOMMENDED NAILING PATTERNS FOR PLYWOOD FOR ON E-BEAM WALL AND ELEVATED DECK SOLUTIONS FASTENER POSITIONS	FACING

Ref: Plywood to a pine wood nailer strip with a deck screw will pull-out at 306 lb (138.8 kg).

Note: Pull-out loads are EFCO laboratory results and do not include a safety factor.

Distributor - If your local distributor does not carry what you want, a U.S. supplier with multiple outlets is SouthernCarlson 1-515-986-5287.

joist is made of lightweight galvanized steel and uses no wood nailer strip.

Use either nails or screws to attach a sheet of plywood to the steel joist.

METABO HPT (HITACHI)

NAIL GÙN MODEL NV65AH2M SINGLE-POUR NAILING PATTERN